


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.03V I:0.1257A P:14.879W PF:0.9860 Freq:60.00Hz Lamp Flux:923.472x1 lm		
NAME: R2ARWT-A930-WT	TYPE: Recessed-mounted Luminaire	HEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: WAC Lighting	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 62.07 lm/W
MODEL		Imax(cd)	841.0	S/MH(C0/180)	1.38	
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.18	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	923.47	η UP,DN(C0-180)	0.0,45.0	
NOMINAL FLUX(lm)	923.472	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,54.9	
LAMPS INSIDE	1	η up(%)	0.1	CIBSE SHR NOM	0.75	
TEST VOLTAGE(V)	120	η down(%)	99.9	CIBSE SHR MAX	0.95	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.2DEG
 Operators:Oliver
 Test Date:2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:2.464m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM


ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum, lamp$
10	241.1	258.8	333.9	468.5	556.7	482.3	341.5	260.0	0- 10	34.17	34.17	3.7,3.7
20	169.8	191.2	301.3	616.9	816.1	655.3	318.7	191.8	10- 20	110.8	145.0	15.7,15.7
30	119.4	135.9	260.8	680.6	760.6	709.5	288.4	137.4	20- 30	186.5	331.5	35.9,35.9
40	85.29	94.81	202.8	558.0	512.9	561.8	232.6	92.83	30- 40	213.3	544.8	59,59
50	50.00	59.48	127.1	363.1	297.5	358.7	140.3	56.77	40- 50	180.1	724.8	78.5,78.5
60	29.15	30.43	58.79	190.0	153.5	171.7	60.25	30.86	50- 60	116.3	841.1	91.1,91.1
70	15.03	14.50	20.89	69.67	66.88	63.79	21.98	14.70	60- 70	58.13	899.2	97.4,97.4
80	3.677	4.158	4.481	10.97	17.50	11.81	4.449	4.121	70- 80	21.14	920.4	99.7,99.7
90	0.2001	0.1404	0.1762	0.2241	0.2668	0.2484	0.1918	0.2157	80- 90	2.409	922.8	99.9,99.9
100	0.0125	0.0051	0	0	0	0	0.0028	0.0191	90-100	0.0741	922.9	99.9,99.9
110	0.0420	0.0304	0.0013	0	0	0	0.0178	0.0457	100-110	0.0118	922.9	99.9,99.9
120	0.1048	0.0825	0.0265	0.0036	0.0034	0.0115	0.0479	0.1256	110-120	0.0304	922.9	99.9,99.9
130	0.2155	0.1658	0.0760	0.0254	0.0341	0.0495	0.1224	0.2530	120-130	0.0744	923.0	99.9,99.9
140	0.2888	0.2253	0.1308	0.0587	0.0811	0.1055	0.2154	0.3603	130-140	0.1189	923.1	100,100
150	0.3422	0.2799	0.2046	0.1176	0.1505	0.1710	0.2870	0.4048	140-150	0.1361	923.2	100,100
160	0.3506	0.3090	0.2671	0.1851	0.2414	0.2468	0.3366	0.4001	150-160	0.1237	923.3	100,100
170	0.3361	0.3422	0.3233	0.2657	0.3521	0.3450	0.3844	0.3890	160-170	0.0881	923.4	100,100
180	0.4298	0.4320	0.3984	0.3423	0.4298	0.4284	0.4157	0.3709	170-180	0.0347	923.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.2DEG
 Operators:Oliver
 Test Date:2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:2.464m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES




LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	122	143
80	210	258
75	320	438
70	436	612
65	514	852
60	579	1178
55	669	1567
50	772	1980
45	895	2350

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.07	1.04	1.01	1.05	1.02	.99	1.01	.98	.96	.97	.95	.93	.93	.92	.90	.88
2.0	.96	.90	.85	.94	.89	.84	.90	.86	.82	.87	.84	.80	.84	.81	.79	.77
3.0	.86	.79	.73	.84	.78	.72	.81	.76	.71	.79	.74	.70	.76	.72	.69	.67
4.0	.77	.69	.63	.76	.69	.63	.73	.67	.62	.71	.66	.61	.69	.64	.61	.59
5.0	.70	.62	.56	.68	.61	.55	.66	.60	.55	.65	.59	.54	.63	.58	.54	.52
6.0	.63	.55	.49	.62	.55	.49	.60	.54	.49	.59	.53	.48	.57	.52	.48	.46
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.54	.48	.43	.53	.47	.43	.41
8.0	.53	.45	.39	.52	.45	.39	.51	.44	.39	.50	.43	.39	.48	.43	.39	.37
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.35	.46	.40	.35	.45	.39	.35	.33
10.0	.45	.37	.32	.44	.37	.32	.43	.37	.32	.43	.36	.32	.42	.36	.32	.30



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.248	.141	.045	.241	.137	.044	.228	.131	.042	.216	.124	.040	.205	.119	.038		
2.0	.242	.132	.041	.235	.130	.040	.224	.125	.039	.214	.120	.038	.204	.115	.036		
3.0	.230	.122	.037	.224	.120	.036	.215	.116	.035	.205	.113	.035	.197	.109	.034		
4.0	.217	.113	.033	.212	.111	.033	.203	.108	.032	.195	.105	.032	.188	.102	.031		
5.0	.204	.104	.030	.200	.103	.030	.192	.100	.029	.185	.098	.029	.178	.095	.029		
6.0	.192	.096	.028	.188	.095	.027	.182	.093	.027	.175	.091	.027	.169	.089	.026		
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.160	.083	.024		
8.0	.171	.084	.023	.168	.083	.023	.162	.081	.023	.157	.080	.023	.152	.078	.023		
9.0	.162	.078	.022	.159	.078	.022	.154	.076	.022	.149	.075	.021	.145	.074	.021		
10.0	.153	.073	.020	.151	.073	.020	.146	.072	.020	.142	.071	.020	.138	.069	.020		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.177	.157	.140	.151	.135	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016	
2.0	.166	.133	.105	.142	.114	.090	.098	.079	.063	.056	.046	.037	.018	.015	.012	
3.0	.157	.115	.081	.135	.099	.070	.093	.069	.049	.053	.040	.029	.017	.013	.009	
4.0	.149	.101	.064	.128	.087	.055	.088	.061	.039	.051	.036	.023	.016	.012	.008	
5.0	.142	.090	.052	.122	.078	.045	.084	.054	.032	.049	.032	.019	.016	.010	.006	
6.0	.136	.082	.043	.117	.071	.037	.080	.049	.026	.047	.029	.016	.015	.010	.005	
7.0	.129	.075	.036	.111	.065	.032	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.123	.069	.031	.106	.060	.027	.074	.042	.019	.043	.025	.011	.014	.008	.004	
9.0	.118	.064	.027	.102	.055	.024	.070	.039	.017	.041	.023	.010	.013	.008	.003	
10.0	.113	.060	.024	.097	.052	.021	.067	.036	.015	.039	.022	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	7.4	8.7	7.6	8.9	9.1	10.6	11.9	10.8	12.1	12.3
3H	8.1	9.3	8.4	9.6	9.8	11.1	12.3	11.3	12.5	12.7
4H	8.3	9.5	8.6	9.7	9.9	11.2	12.3	11.5	12.6	12.8
6H	8.3	9.4	8.7	9.7	10.0	11.2	12.3	11.5	12.5	12.8
8H	8.3	9.4	8.7	9.7	9.9	11.1	12.2	11.5	12.5	12.8
12H	8.3	9.3	8.6	9.6	9.9	11.1	12.1	11.4	12.4	12.7
4H 2H	7.7	8.9	8.0	9.1	9.4	10.5	11.7	10.8	11.9	12.2
3H	8.6	9.6	8.9	9.9	10.2	11.1	12.1	11.5	12.4	12.7
4H	8.9	9.8	9.2	10.1	10.4	11.3	12.2	11.7	12.5	12.9
6H	9.0	9.8	9.4	10.1	10.5	11.4	12.2	11.8	12.5	12.9
8H	9.0	9.7	9.4	10.1	10.5	11.4	12.1	11.8	12.5	12.9
12H	9.0	9.6	9.4	10.0	10.4	11.3	12.0	11.8	12.4	12.8
8H 4H	8.9	9.7	9.3	10.0	10.4	11.3	12.0	11.7	12.4	12.8
6H	9.1	9.7	9.6	10.1	10.6	11.4	12.0	11.8	12.4	12.8
8H	9.2	9.7	9.6	10.1	10.6	11.4	11.9	11.9	12.4	12.8
12H	9.2	9.6	9.6	10.1	10.5	11.4	11.8	11.9	12.3	12.8
12H 4H	8.9	9.6	9.3	10.0	10.4	11.2	11.9	11.7	12.3	12.7
6H	9.1	9.6	9.6	10.1	10.5	11.4	11.9	11.8	12.3	12.8
8H	9.2	9.6	9.6	10.1	10.5	11.4	11.8	11.9	12.3	12.8
Variations with the observer position at spacings:										
S = 1.0H	+ 0.6 / - 0.8					+ 1.3 / - 0.9				
1.5H	+ 0.4 / - 0.5					+ 2.0 / - 1.6				
2.0H	+ 0.9 / - 0.8					+ 3.4 / - 2.5				

CIE Pub.117, 923.5 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = -0.3$)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:


UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	66	55	49	65	55	49	64	55	49	43
0.80	76	66	60	75	65	59	73	65	59	53
1.00	84	75	69	83	74	68	81	75	68	62
1.25	90	82	76	89	81	76	87	80	75	69
1.50	95	87	81	93	86	81	91	84	80	73
2.00	101	94	89	99	93	88	96	91	86	80
2.50	104	97	93	102	96	92	98	94	90	83
3.00	106	101	97	104	99	95	101	97	93	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	106	103	105	102	100	91
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004						Suspended			SHRNOM = 1.25	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:


ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.2DEG
Operators: Oliver
Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 2.464m [K=1.0000]
Remarks:

AAI CURVES



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.2DEG
Operators: Oliver
Test Date: 2018-04-03

```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:2.464m [K=1.0000]
Remarks:

```

ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.2DEG
Operators: Oliver
Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 2.464m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.03V I:0.1257A P:14.879W PF:0.9860 Freq:60.00Hz Lamp Flux:923.472x1 lm		
NAME: R2ARWT-A930-WT	TYPE: Recessed-mounted Luminaire	HEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: WAC Lighting	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1483
L_0~180(75)av	911
L_0~180(85)av	231
L_90~270(65)av	865
L_90~270(75)av	446
L_90~270(85)av	143
L_45(65)av	1615
L_45(75)av	847
L_45(85)av	134

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.2DEG
Operators: Oliver
Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 2.464m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	348	348	348	348	348	348	348	348	348	348	348	348	348	348	348	348			
5	287	289	300	318	343	373	403	426	437	430	408	378	347	321	301	289			
10	241	245	259	288	334	397	469	530	557	538	482	408	342	292	260	243			
15	202	209	224	257	320	420	546	650	699	668	570	441	332	261	224	206			
20	170	176	191	227	301	438	617	755	816	781	655	472	319	233	192	175			
25	141	146	162	199	282	454	673	793	836	813	712	500	305	204	163	145			
30	119	123	136	171	261	457	681	742	761	757	709	512	288	176	137	122			
35	106	106	114	145	235	440	637	647	637	651	653	495	264	149	113	104			
40	85.3	91.0	94.8	119	203	394	558	529	513	533	562	440	233	123	92.8	89.1			
45	63.7	67.7	79.0	95.8	166	329	460	414	396	421	461	358	189	96.9	75.3	68.0			
50	50.0	51.0	59.5	74.5	127	251	363	318	297	320	359	265	140	74.0	56.8	50.8			
55	38.6	39.7	42.4	54.1	89.8	175	272	236	219	233	258	177	95.6	54.6	42.2	38.4			
60	29.2	29.8	30.4	37.8	58.8	110	190	170	154	163	172	108	60.2	38.2	30.9	29.4			
65	21.9	21.9	21.7	25.7	35.9	64.4	120	115	103	111	109	62.8	37.2	26.1	22.1	21.3			
70	15.0	14.7	14.5	16.6	20.9	34.1	69.7	73.3	66.9	70.8	63.8	34.1	22.0	17.2	14.7	14.1			
75	8.33	8.28	8.76	9.83	11.3	17.2	37.0	42.3	38.8	39.9	33.0	16.9	11.8	10.2	8.91	8.22			
80	3.68	3.86	4.16	4.41	4.48	5.38	11.0	15.4	17.5	17.2	11.8	5.25	4.45	4.45	4.12	3.88			
85	1.07	1.16	1.30	1.34	1.25	1.10	1.06	1.20	2.95	1.83	1.01	1.09	1.25	1.35	1.31	1.26			
90	0.20	0.17	0.14	0.19	0.18	0.19	0.22	0.20	0.27	0.28	0.25	0.24	0.19	0.21	0.22	0.22			
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.02			
100	0.01	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.02			
105	0.03	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.01	0.03	0.03			
110	0.04	0.04	0.03	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.03	0.05	0.05			
115	0.07	0.06	0.05	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.05	0.08	0.08			
120	0.10	0.10	0.08	0.05	0.03	0.01	0.00	0.00	0.00	0.00	0.01	0.02	0.05	0.09	0.13	0.14			
125	0.16	0.15	0.12	0.08	0.05	0.03	0.01	0.01	0.02	0.02	0.03	0.05	0.08	0.14	0.19	0.21			
130	0.22	0.20	0.17	0.12	0.08	0.05	0.03	0.02	0.03	0.04	0.05	0.07	0.12	0.19	0.25	0.29			
135	0.26	0.24	0.20	0.15	0.10	0.07	0.04	0.03	0.06	0.06	0.08	0.11	0.17	0.25	0.32	0.37			
140	0.29	0.27	0.23	0.18	0.13	0.09	0.06	0.04	0.08	0.09	0.11	0.15	0.22	0.29	0.36	0.42			
145	0.32	0.29	0.26	0.21	0.17	0.12	0.09	0.07	0.11	0.11	0.14	0.18	0.26	0.33	0.39	0.45			
150	0.34	0.31	0.28	0.24	0.20	0.16	0.12	0.10	0.15	0.15	0.17	0.22	0.29	0.35	0.40	0.45			
155	0.35	0.32	0.30	0.27	0.24	0.19	0.15	0.12	0.19	0.19	0.21	0.25	0.31	0.37	0.40	0.43			
160	0.35	0.32	0.31	0.29	0.27	0.23	0.19	0.15	0.24	0.24	0.25	0.29	0.34	0.38	0.40	0.41			
165	0.34	0.32	0.32	0.32	0.30	0.26	0.23	0.19	0.29	0.29	0.29	0.32	0.36	0.39	0.40	0.39			
170	0.34	0.33	0.34	0.34	0.32	0.30	0.27	0.24	0.35	0.35	0.34	0.37	0.38	0.40	0.39	0.36			
175	0.41	0.41	0.41	0.39	0.36	0.34	0.31	0.28	0.41	0.41	0.40	0.41	0.41	0.40	0.39	0.36			
180	0.43	0.43	0.43	0.42	0.40	0.37	0.34	0.32	0.43	0.43	0.43	0.43	0.42	0.40	0.37	0.34			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.2DEG
 Operators: Oliver
 Test Date: 2018-04-03

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 2.464m [K=1.0000]
 Remarks: