


Model: 866

120V Track MR16 Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Low Voltage luminaire with die-cast aluminum construction and swivel yoke for precise aiming.

FEATURES

- Includes a translucent etched glass shade
- Use with a frosted back lamp to illuminate the shade with a soft white glow
- Screw and swivel yoke for precise aiming
- 350° horizontal rotation and 90° vertical tilt
- Dimmable
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum track head with polycarbonate transformer case and track adapter. Bi-pin ceramic socket for MR16 lamp.

Finish: Powder coat paint. Available in Black (BK), Brushed Nickel (BN) and White (WT).

Transformer: 20W minimum load (1W minimum load available. Consult factory for more details).

Lamp: 866 model uses 12V MR16G, 50W max lamp (not included). 866L model uses 12V MR16G, 75W max (not included).

Dimming: With electronic low voltage (ELV) dimmer, lamp dims to 1%.

Standards: UL & CUL Listed.

ORDER NUMBER

| System | Model # | Power | Lamp | Finish |
|----------------|---------|-------|---------|----------|
| LHT L Track | 866 | 50W | Halogen | WT White |
| HHT H Track | 866L | 75W | Halogen | |
| JHT J/J2 Track | | | | |




Example: LHT-866-WT

ACCESSORIES (WITH USE OF LENS CLIP)

| | | | | |
|------------|------------|--------|----------------------|--------------------|
| Color Lens | AMB | Amber | UV Filter | LENS-16-UVF |
| | BLU | Blue | Frosted Lens | LENS-16-FR |
| | GRN | Green | Spread Lens | LENS-16-SPR |
| | RED | Red | Beam Elongating Lens | LENS-16-BEL |
| | YEL | Yellow | Honeycomb Louver | LENS-16-HCL |

LENS CLIP



WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585