


IRIX – model: DR-356

Crystal Collection: Beauty Spots™

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Beauty Spots™ series are low voltage surface mount fixtures designed for use in drywall ceilings, grid ceilings, walls, or displays. Clear shades fit over the lamp and are retained by a spring band.

FEATURES

- Sold as a complete unit - housing and trim
- Use 12V/24V remote electronic or magnetic transformer (order separately) see next pages for complete transformer spec
- Easily mounted on suspended or finished ceilings
- Can be used individually as accent pieces or grouped together
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Canopy faceplate is chrome plated, wiring compartment is steel, painted black

Light Source: LED 4.3W or Xenon Bi-Pin 20W with canopy

Mounting: No screws, nails or hardware required, flat "wing" springs expand against the cut out hole to hold fixture against the surface (2 3/8" cut out hole)


Integral wiring compartment with standard size knock out hole on top. When using a class II power supply, side hole may be used for wire entry

Dimming: ELV Dimming: 100%-10% (Xenon only)

Standards: UL & cUL Listed

Integral LED

* Dimming is not recommended




DR-356LED-CL/CH Irix

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	150	24V	4.5 W	50,000 hours	Clear / Chrome	2 3/8"

		Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
Remote Transformer for Integral LED	EN-2460-RB2	120V	24V, 60W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	12 per transformer	30'
	EN-24100-RB2	120V	24V, 96W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	21 per transformer	40'

12V Xenon Bi-Pin

* Dimmable with compatible dimmer match to power supply



DR-365-CL/CH Irix

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	200	12V, 24V	20 W	10,000 hours	Clear/ Chrome	2 3/8"

		Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
Remote Transformer for Xenon Bi-pin	EN-1260-RB2	120V	12V, 60W (class 2)	1W	6 5/8" x 1 5/8" x 1 1/8"	3	25'
	EN-12100-RB-AR	120V	12V, 100W	1W	6 1/4" x 3" x 1 5/8"	5	30'
	EN-12150-RB-AR	120V	12V, 150W	1W	6 1/4" x 3" x 1 5/8"	7	35'

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585