


# TUBE ARCHITECTURAL DS-CD05

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

### FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

### SPECIFICATIONS

**Input:** Universal voltage 120V - 277VAC, 50/60Hz  
**Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)  
 0-10V: 100% - 1% (120-277V)  
**Light Source:** High output 3 Step Mac Adam Ellipse COB  
 Rated life of 60,000 hours at L70  
**Finish:** Electrostatically powder coated, white, black, bronze and graphite  
**Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with \*)  
**Operating Temp:** -13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

Diameter	Watt	Beam	Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD05	27W	S Spot	18°	927	2700K	90	1680	8526	62		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
				27*	2700K	85	1800	9151	67		
				930	3000K	90	1700	8639	63		
				30*	3000K	85	1995	10126	74		
				35*	3500K	85	2190	11118	81		
				40*	4000K	85	2260	11483	84		
		N Narrow	25°	927	2700K	90	1730	5513	64		
				27*	2700K	85	1855	5918	69		
				930	3000K	90	1750	5587	65		
				30*	3000K	85	2055	6548	76		
				35*	3500K	85	2255	7190	84		
				40*	4000K	85	2330	7426	86		
		F Flood	33°	927	2700K	90	1725	4246	64		
				27*	2700K	85	1850	4557	69		
				930	3000K	90	1745	4302	65		
				30*	3000K	85	2045	5043	73		
				35*	3500K	85	2245	5537	83		
				40*	4000K	85	2320	5719	86		

DS-CD05- \_\_\_\_\_ - \_\_\_\_\_

Example: DS-CD05-N927-BK

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122


Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760

# TUBE ARCHITECTURAL DS-CD06

LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

## FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

## SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)  
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with \*)
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

## ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD06	36W	S Spot	19°	927	2700K	90	1875	8911	51		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
				27*	2700K	85	2400	11392	65		
				930	3000K	90	2000	9500	54		
				30*	3000K	85	2170	10317	59		
				35*	3500K	85	2500	11884	68		
		40*	4000K	85	2450	11639	66				
		N Narrow	30°	927	2700K	90	1830	4642	49		
				27*	2700K	85	2340	5935	63		
				930	3000K	90	1950	4949	53		
				30*	3000K	85	2120	5374	57		
				35*	3500K	85	2440	6191	66		
		40*	4000K	85	2390	6063	65				
		F Flood	40°	927	2700K	90	1840	3310	50		
				27*	2700K	85	2355	4231	64		
				930	3000K	90	1965	3528	53		
30*	3000K			85	2130	3832	58				
35*	3500K			85	2455	4414	66				
40*	4000K	85	2405	4323	65						

DS-CD06-\_\_\_\_\_-\_\_\_\_\_-

Example: DS-CD06-N927-BK

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122


Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# TUBE ARCHITECTURAL DS-CD08

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent lighting. Comes in various light beam angle options.

### FEATURES

- High performance exterior rated LED ceiling light
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

### SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)  
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.0 rated (labeled with \*)
- Operating Temp:** -13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

Diameter	Watt	Beam Angle	Color	Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
DS-CD08	48W	S Spot 18°	927	2700K	90	3075	11830	64		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
			27*	2700K	85	3540	13616	74		
			930	3000K	90	2975	11443	62		
			30*	3000K	85	3615	13904	75		
			35*	3500K	85	3855	14822	80		
			40*	4000K	85	3915	15054	82		
	48W	N Narrow 21°	927	2700K	90	3075	16383	64		
			27*	2700K	85	3540	18857	74		
			930	3000K	90	2975	15847	62		
			30*	3000K	85	3615	19255	75		
			35*	3500K	85	3855	20526	80		
			40*	4000K	85	3915	20847	82		
	48W	F Flood 34°	927	2700K	90	3035	6200	63		
			27*	2700K	85	3495	7136	73		
			930	3000K	90	2935	5997	61		
			30*	3000K	85	3570	7287	74		
			35*	3500K	85	3805	7768	79		
			40*	4000K	85	3865	7890	81		

DS-CD08-\_\_\_\_\_ - \_\_\_\_\_

Example: DS-CD08-N927-BK

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760