

TUBE ARCHITECTURAL DS-WS05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- Energy Star® rated (labeled with *)
- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 10% (120V only)
0-10V: 100% - 5% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
<p>DS-WS05 5" 27W</p>	S927S	2700K	90	1680	8526	62	Straight up or down 18°		BK Black WT White BZ Bronze GH Graphite
	S827S	2700K	85	1800	9151	67			
	S930S	3000K	90	1700	8639	63			
	S830S	3000K	85	1995	10126	74			
	S835S	3500K	85	2190	11118	81			
	S840S	4000K	85	2260	11483	84			
	N927S	2700K	90	1730	5513	64	Straight up or down 25°		
	N827S	2700K	85	1855	5918	69			
	N930S	3000K	90	1750	5587	65			
	N830S	3000K	85	2055	6548	76			
	N835S	3500K	85	2255	7190	84			
	N840S	4000K	85	2330	7426	86			
	F927S	2700K	90	1725	4246	64	Straight up or down 33°		
	F827S	2700K	85	1850	4557	69			
	F930S	3000K	90	1745	4302	65			
	F830S	3000K	85	2045	5043	76			
	F835S	3500K	85	2245	5537	83			
	F840S	4000K	85	2320	5719	86			
	F927A	2700K	90	1815		67	Away from the wall		
	F827A*	2700K	85	1950	n/a	72			
F930A	3000K	90	1840	n/a	68				
F830A*	3000K	85	2155	n/a	80				
F835A*	3500K	85	2370	n/a	88				
F840A*	4000K	85	2445	n/a	91				
F927B	2700K	90	1815		67	Towards the wall			
F827B*	2700K	85	1950	n/a	72				
F930B	3000K	90	1840	n/a	68				
F830B*	3000K	85	2155	n/a	80				
F835B*	3500K	85	2370	n/a	88				
F840B*	4000K	85	2445	n/a	91				

DS-WS05-_____ - _____

Example: **DS-WS05-F930A-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-WS06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- Energy Star® rated (labeled with *)
- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 10% (120V only)
0-10V: 100% - 5% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
	S927S	2700K	90	1875	8911	52	Straight up or down 19°	
	S827S	2700K	85	2400	11392	67		
	S930S	3000K	90	2000	9500	56		
	S830S	3000K	85	2170	10317	60		
	S835S	3500K	85	2500	11884	69		
	S840S	4000K	85	2450	11639	68		
	N927S	2700K	90	1830	4642	51	Straight up or down 30°	
	N827S	2700K	85	2340	5935	65		
	N930S	3000K	90	1950	4949	54		
	N830S	3000K	85	2120	5374	59		
	N835S	3500K	85	2440	6191	68		
	N840S	4000K	85	2390	6063	66		
F927S	2700K	90	1840	3310	51	Straight up or down 40°		
F827S	2700K	85	2355	4231	65			
F930S	3000K	90	1965	3528	55			
F830S	3000K	85	2130	3832	59			
F835S	3500K	85	2455	4414	68			
F840S	4000K	85	2405	4323	67			
F927A	2700K	90	2225		62	Away from the wall		
F827A*	2700K	85	2840		79			
F930A	3000K	90	2370	n/a	66			
F830A*	3000K	85	2575		72			
F835A*	3500K	85	2965		82			
F840A*	4000K	85	2905		81			
F927B	2700K	90	2225		62	Towards the wall		
F827B*	2700K	85	2840		79			
F930B	3000K	90	2370	n/a	66			
F830B*	3000K	85	2575		72			
F835B*	3500K	85	2965		82			
F840B*	4000K	85	2905		81			

- BK** Black
- WT** White
- BZ** Bronze
- GH** Graphite

DS-WS06-_____ - _____

Example: DS-WS06-F930A-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-WS08

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- Energy Star® rated (labeled with *)
- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty


SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 10% (120V only)
 0-10V: 100% - 5% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 65,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
	8" 48W	S927S 2700K	90	3075	16382	64	Straight up or down 18°		
		S827S 2700K	85	3540	18856	74			
		S930S 3000K	90	2975	15847	62			
		S830S 3000K	85	3615	19254	75			
		S835S 3500K	85	3855	20525	80			
		S840S 4000K	85	3915	20847	82			
	8" 48W	8" 48W	N927S 2700K	90	3075	11830	64	Straight up or down 21°	
			N827S 2700K	85	3540	13616	74		
			N930S 3000K	90	2975	11443	62		
			N830S 3000K	85	3615	13903	75		
			N835S 3500K	85	3850	14821	80		
			N840S 4000K	85	3910	15053	82		
8" 48W	8" 48W	F927S 2700K	90	3035	6200	64	Straight up or down 35°		
		F827S 2700K	85	3495	7136	73			
		F930S 3000K	90	2935	5997	50			
		F830S 3000K	85	3565	7287	74			
		F835S 3500K	85	3805	7768	79			
		F840S 4000K	85	3806	7889	80			
8" 48W	8" 48W	F927A 2700K	90	2870		60	Away from the wall		
		F827A* 2700K	85	3305		69			
		F930A 3000K	90	2775	n/a	58			
		F830A* 3000K	85	3375		70			
		F835A* 3500K	85	3595		75			
		F840A* 4000K	85	3655		76			
8" 48W	8" 48W	F927B 2700K	90	2870		60	Towards the wall		
		F827B* 2700K	85	3305		69			
		F930B 3000K	90	2775	n/a	58			
		F830B* 3000K	85	3375		70			
		F835B* 3500K	85	3595		75			
		F840B* 4000K	85	3655		76			

BK Black
WT White
BZ Bronze
GH Graphite



Example: DS-WS08-F930A-WT

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WD05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 10% (120V only)
 0-10V: 100% - 5% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
	S827S	2700K	85	1680 x 2	8526 x 2	62 x 2	Straight up and down 18°		BK Black WT White BZ Bronze GH Graphite
	S927S	2700K	90	1800 x 2	9151 x 2	67 x 2			
	S830S	3000K	85	1700 x 2	8639 x 2	63 x 2			
	S930S	3000K	90	1995 x 2	10126 x 2	74 x 2			
	S835S	3500K	85	2190 x 2	11118 x 2	81 x 2			
	S840S	4000K	85	2260 x 2	11483 x 2	84 x 2			
	N827S	2700K	85	1730 x 2	5513 x 2	64 x 2	Straight up and down 25°		
	N927S	2700K	90	1855 x 2	5918 x 2	69 x 2			
	N830S	3000K	85	1750 x 2	5587 x 2	65 x 2			
	N930S	3000K	90	2055 x 2	6548 x 2	76 x 2			
	N835S	3500K	85	2255 x 2	7190 x 2	84 x 2			
	N840S	4000K	85	2330 x 2	7426 x 2	86 x 2			
	F827S	2700K	85	1725 x 2	4246 x 2	64 x 2	Straight up and down 33°		
	F927S	2700K	90	1850 x 2	4557 x 2	69 x 2			
	F830S	3000K	85	1745 x 2	4302 x 2	65 x 2			
	F930S	3000K	90	2045 x 2	5043 x 2	76 x 2			
	F835S	3500K	85	2245 x 2	5537 x 2	83 x 2			
	F840S	4000K	85	2320 x 2	5719 x 2	86 x 2			
	F827A	2700K	85	1815 x 2		67 x 2	Away from the wall		
	F927A	2700K	90	1950 x 2	n/a	72 x 2			
	F830A	3000K	85	1840 x 2	n/a	68 x 2			
	F930A	3000K	90	2155 x 2	n/a	80 x 2			
	F835A	3500K	85	2370 x 2	n/a	88 x 2			
	F840A	4000K	85	2445 x 2	n/a	91 x 2			
F827B	2700K	85	1815 x 2		67 x 2	Towards the wall			
F927B	2700K	90	1950 x 2	n/a	72 x 2				
F830B	3000K	85	1840 x 2	n/a	68 x 2				
F930B	3000K	90	2155 x 2	n/a	80 x 2				
F835B	3500K	85	2370 x 2	n/a	88 x 2				
F840B	4000K	85	2445 x 2	n/a	91 x 2				
F827C	2700K	85	1815 x 2		67 x 2	One side each			
F927C	2700K	90	1950 x 2	n/a	72 x 2				
F830C	3000K	85	1840 x 2	n/a	68 x 2				
F930C	3000K	90	2155 x 2	n/a	80 x 2				
F835C	3500K	85	2370 x 2	n/a	88 x 2				
F840C	4000K	85	2445 x 2	n/a	91 x 2				

DS-WD05- _____ - _____ Example: **DS-WD05-F930A-WT**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WD06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 10% (120V only)
 0-10V: 100% - 5% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 70,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WD06 6" 35W x 2</p>	S827S	2700K	85	1875 x 2	8911	52 x 2	Straight up and down 19°	
	S927S	2700K	90	2400 x 2	11392	67 x 2		
	S830S	3000K	85	2000 x 2	9500	56 x 2		
	S930S	3000K	90	2170 x 2	10317	60 x 2		
	S835S	3500K	85	2500 x 2	11884	69 x 2		
	S840S	4000K	85	2450 x 2	11639	68 x 2		
	N827S	2700K	85	1830 x 2	4642	51 x 2	Straight up and down 30°	
	N927S	2700K	90	2340 x 2	5935	65 x 2		
	N830S	3000K	85	1950 x 2	4949	54 x 2		
	N930S	3000K	90	2120 x 2	5374	59 x 2		
	N835S	3500K	85	2440 x 2	6191	68 x 2		
	N840S	4000K	85	2390 x 2	6063	66 x 2		
	F827S	2700K	85	1840 x 2	3310	51 x 2	Straight up and down 40°	
	F927S	2700K	90	2355 x 2	4231	65 x 2		
	F830S	3000K	85	1965 x 2	3528	55 x 2		
	F930S	3000K	90	2130 x 2	3832	59 x 2		
	F835S	3500K	85	2455 x 2	4414	68 x 2		
	F840S	4000K	85	2405 x 2	4323	67 x 2		
	F827A	2700K	85	2225 x 2		62 x 2	Away from the wall	
	F927A	2700K	90	2840 x 2	n/a	79 x 2		
	F830A	3000K	85	2370 x 2	n/a	66 x 2		
	F930A	3000K	90	2575 x 2	n/a	72 x 2		
	F835A	3500K	85	2965 x 2	n/a	82 x 2		
	F840A	4000K	85	2905 x 2	n/a	81 x 2		
F827B	2700K	85	2225 x 2		62 x 2	Towards the wall		
F927B	2700K	90	2840 x 2	n/a	79 x 2			
F830B	3000K	85	2370 x 2	n/a	66 x 2			
F930B	3000K	90	2575 x 2	n/a	72 x 2			
F835B	3500K	85	2965 x 2	n/a	82 x 2			
F840B	4000K	85	2905 x 2	n/a	81 x 2			
F827C	2700K	85	2225 x 2		62 x 2	One side each		
F927C	2700K	90	2840 x 2	n/a	79 x 2			
F830C	3000K	85	2370 x 2	n/a	66 x 2			
F930C	3000K	90	2575 x 2	n/a	72 x 2			
F835C	3500K	85	2965 x 2	n/a	82 x 2			
F840C	4000K	85	2905 x 2	n/a	81 x 2			

BK	Black	
WT	White	
BZ	Bronze	
GH	Graphite	

DS-WD06- _____ - _____ Example: **DS-WD06-F930A-WT**

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WD08

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 10% (120V only)
 0-10V: 100% - 5% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 65,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed, Energy Star 2.0 (offerings marked with an asterisk)

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
	8"	48W x 2	S827S 2700K 85 3540 x 2 18856 74 x 2	18856	74 x 2	Straight up and down 18°		BK Black WT White BZ Bronze GH Graphite
			S927S 2700K 90 3075 x 2 16382 64 x 2					
			S830S 3000K 85 3615 x 2 19254 75 x 2					
			S930S 3000K 90 2975 x 2 15847 62 x 2					
			S835S 3500K 85 3855 x 2 20525 80 x 2					
			S840S 4000K 85 3915 x 2 20817 82 x 2					
	8"	48W x 2	N827S 2700K 85 3540 x 2 13616 74 x 2	13616	74 x 2	Straight up and down 21°		
			N927S 2700K 90 3075 x 2 11830 64 x 2					
			N830S 3000K 85 3615 x 2 13903 75 x 2					
			N930S 3000K 90 2975 x 2 11443 62 x 2					
			N835S 3500K 85 3855 x 2 14821 80 x 2					
			N840S 4000K 85 3915 x 2 15053 82 x 2					
	8"	48W x 2	F827S 2700K 85 3495 x 2 7136 73 x 2	7136	73 x 2	Straight up and down 35°		
			F927S 2700K 90 3035 x 2 6200 64 x 2					
			F830S 3000K 85 3565 x 2 7287 74 x 2					
			F930S 3000K 90 2935 x 2 5997 50 x 2					
			F835S 3500K 85 3850 x 2 7768 79 x 2					
			F840S 4000K 85 3910 x 2 7889 80 x 2					
	8"	48W x 2	F827A 2700K 85 3305 x 2 69 x 2	n/a	69 x 2	Away from the wall		
			F927A 2700K 90 2870 x 2 60 x 2					
F830A 3000K 85 3375 x 2 70 x 2								
F930A 3000K 90 2775 x 2 58 x 2								
F835A 3500K 85 3595 x 2 75 x 2								
F840A 4000K 85 3655 x 2 76 x 2								
8"	48W x 2	F827B 2700K 85 3305 x 2 69 x 2	n/a	69 x 2	Towards the wall			
		F927B 2700K 90 2870 x 2 60 x 2						
		F830B 3000K 85 3375 x 2 70 x 2						
		F930B 3000K 90 2775 x 2 58 x 2						
		F835B 3500K 85 3595 x 2 75 x 2						
		F840B 4000K 85 3655 x 2 76 x 2						
8"	48W x 2	F827C 2700K 85 3305 x 2 69 x 2	n/a	69 x 2	One side each			
		F927C 2700K 90 2870 x 2 60 x 2						
		F830C 3000K 85 3375 x 2 70 x 2						
		F930C 3000K 90 2775 x 2 58 x 2						
		F835C 3500K 85 3595 x 2 75 x 2						
		F840C 4000K 85 3655 x 2 76 x 2						

DS-WD08-

Example: DS-WD08-F930A-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760