

RUBIX - model: FM-W25

LED Ceiling Mount

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION






Precise engineering using the latest energy efficient LED technology with a built-in reflector for superior optics; An appealing cylindrical profile with a powerful LED down light perfect for accent and wall wash lighting.


FEATURES

- Wall or ceiling mount
- IP65 Rated, ETL & cETL Wet Location listed
- Die-Cast aluminum construction
- Universal voltage Input (120V - 277V)
- Dimming: ELV (120V) or 0-10V

SPECIFICATIONS

Construction: Aluminum with etched glass
Power: Integral driver in luminaire, 120V - 277V input
Light Source: High output LED
Mounting: Mounts directly to junction box
Dimming: 0-10V Dimming: 100%-10%
 ELV Dimming: 100%-15% (120V only)
Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT)
Color Temp: 3000K
CRI: 90
Rated Life: 70,000 hours
Standards: IP65 Rated, ETL & cETL Wet Location listed, Title 24 JA8-2016
 Compliant, Dark Sky friendly

	Beam	Voltage	Watt	Lumens	Finish
 	FM-W2505 86°	120V - 277V	16W	945	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White 
 	FM-W2510 95°	120V - 277V	30W	2140	



Example: **FM-W2510-WT**

WAC Lighting

www.waclighting.com
 Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
 Phone (800) 526.2588 • Fax (800) 526.2585