HR-3LED-H18D-A


3.5" Tesla[™] New Construction Housing

Non-IC – Airtight

WAC LIGHTING

Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	

Location:

SPECIFICATIONS

PRODUCT DESCRIPTION

Non-IC, airtight, new construction housing. For use with HR-3LED Tesla 3.5" series trims.

FEATURES

- Airtight
- Cutout: 45%"
- 120 277 VAC Input
- · Provided with push-in wire connector for easy installation
- Accommodates ceiling thickness from ½"-¾"
- · Does not accomodate adjustements
- 5 year WAC Lighting product warranty

ORDER NUMBER

HR-3LED-H18D-A

New Construction Non-IC, Airtight

HR-3LED-H18D-A

Construction: Housing and junction box are 20 gauge steel. Hanger bars are heavy gauge galvanized steel.

J-Box: Three knockouts provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120 - 277VAC input, 21.5W output. Power factor >0.9 Dimming with thermal protection.

Mounting: Supplied with hanger bars, adjustable from 14¹/₂"-24¹/₂" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surfaces from $\frac{1}{2}$ "- $\frac{3}{4}$ " thick. 45%" cutout hole.

Dimming: 100%-0% with 0-10V dimmer (120V - 277V) 100%-5% with Electronic Low Voltage (ELV) dimmer (120V only)

Standards: Non-IC - insulation must be kept at least 3" away from the housing Airtight ETL & cETL Listed.

COMPATIBLE TRIMS Does not accomodate adjustments. See individual trim spec sheets for complete order number and specifications.

la Pro 3.5"		Tesla 3.5"	
HR3LD-ET118P Series Round, High Brightness Wet Location Listed Energy Star®	HR3LEDT718P Series Square, Open Reflector Energy Star®	HR-3LD-ET118 Series Round, High Brightness Energy Star®	HR-3LED-T218 Series Round, Shower Light Wet Location Listed
HR3LEDT118P Series Round, Downlight Energy Star®	HR3LEDT518P Series Square, 0°- 30° Adjustable Energy Star®	HR-3LED-T118 Series Round. Open Reflector	HR-3LED-T718 Series Square, Open Reflector
HR3LEDT318P Series Round, 0°- 30° Adjustable Energy Star®		HR-3LED-T318 Series Round, 0°- 30° Adjustable	HR-3LED-T818 Series Square, Shower Light Wet Location Listed
57	HR3LEDT818P Series		WEI LOCUTION LISTED
HR3LEDT218P Series Round, Shower Light Wet Location Listed Energy Star®	Square, Shower Light Wet Location Listed Energy Star®	HR-3LED-T618 <i>Round, Pin Hole</i> 0°- 30° Adjustable	HR-3LED-T518 Series Square, 0°- 30° Adjustable

waclighting.com Phone (800) 526.2588 (800) 526.2585 Fax

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUN 2016