


HR-3LED-H18D

3.5" Tesla™ New Construction Housing
IC-Rated – Airtight

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION


IC-Rated, airtight, new construction housing.
For use with HR-3LED Tesla 3.5" series trims.

FEATURES

- IC-Rated, Airtight
- Emergency Backup Battery lasts 90 minutes
- Provided with push-in wire connector for easy installation
- Accommodates ceiling thickness from 1/2"-3/4"
- Allows adjustment in any direction
- 5 year WAC Lighting product warranty

ORDER NUMBER

HR-3LED-H18D-ICA	New Construction IC-Rated, Airtight	120V-277V
HR-3LED-H18D-ICAC	New Construction IC-Rated, Airtight Chicago Plenum	120V-277V
HR-3LED-H18D-EMICA	New Construction IC-Rated, Airtight Emergency Backup Battery	120V
HR3LED-H18D-EMICAF	New Construction IC-Rated, Airtight Emergency Backup Battery	277V



Example: **HR-3LED-H18D-ICAC**

SPECIFICATIONS

Construction: Housing and junction box are 20 gauge steel.
Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 21.5W output
Power factor >0.9 Dimming with thermal protection.

Mounting: Supplied with hanger bars, adjustable between 10 1/8"-24 1/2" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surfaces from 1/2"-3/4" thick. 4 5/8" cutout hole.

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Standards: IC-Rated- Suitable for direct contact with insulation.
Airtight
ETL & cETL Listed.
HR-3LED-H18D1-ICAC is Chicago Plenum Rated

COMPATIBLE TRIMS Allows adjustment in any direction. See individual trim spec sheets for complete order number and specifications

Tesla Pro 3.5"

HR3LD-ET118P Series Round, High Brightness Wet Location Listed Energy Star®	HR3LEDT718P Series Square, Open Reflector Energy Star®
HR3LEDT118P Series Round, Downlight Energy Star®	HR3LEDT518P Series Square, 0°- 30° Adjustable Energy Star®
HR3LEDT318P Series Round, 0°- 30° Adjustable Energy Star®	HR3LEDT918P Series Square, 30°- 45° Adjustable Energy Star®
HR3LEDT418P Series Round, 30°- 45° Adjustable Energy Star®	HR3LEDT818P Series Square, Shower Light Wet Location Listed Energy Star®
HR3LEDT218P Series Round, Shower Light Wet Location Listed Energy Star®	

Tesla 3.5"

HR-3LD-ET118 Series Round, High Brightness Energy Star®	HR-3LED-T218 Series Round, Shower Light Wet Location Listed
HR-3LED-T118 Series Round, Open Reflector	HR-3LED-T718 Series Square, Open Reflector
HR-3LED-T318 Series Round, 0°- 30° Adjustable	HR-3LED-T818 Series Square, Shower Light Wet Location Listed
HR-3LED-T618 Round, Pin Hole 0°- 30° Adjustable	HR-3LED-T518 Series Square, 0°- 30° Adjustable
HR-3LED-T418 Series Round, 30°- 45° Adjustable	HR-3LED-T918 Series Square, 30°- 45° Adjustable

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760