




# HR-86, HR-88

## Low Voltage Button Lights

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Designed with a low profile and shallow installation depth for tight spaces, the innovative xenon and halogen Button Lights™ offer a low profile and shallow installation depth can be surface mounted or recessed for a built-in look within shelves, under and inside cabinets, étagères, curios and displays in fine residential and retail environments.

### FEATURES

- All steel construction
- Cutout template included for recessed installations
- Supplied with 72" wires
- Low profile and shallow installation depth
- Recessed or surface mounting
- Lamp included
- Dimmable with electronic low voltage dimmers.
- Must be used with a Class 2 power supply

### SPECIFICATIONS

**Materials:** Cast aluminum inner housing with a decorative outer steel housing included for surface mounting; outer housing is discarded when used as a recessed fixture. The socket is a bi-pin ceramic with 72" 20 gauge fiberglass lead wires.

**Transformers:** Transformer required (order separately).

**Light Source:** 12V/20W Xenon/Halogen Bi-Pin included

**Power:** 12V/24V 20W max

**Mounting:** *Recessed*– 2 3/8" cutout hole. Compression springs hold fixture firmly in place.

*Surface*– Screw housing cover to surface, compress springs and insert into cover.


*Not recommended for use in ceiling.*

**Finish:** Black (BK), Dark Bronze (DB) and White (WT) powder coat, electroplated Brushed Nickel (BN), Copper Bronze (CB) and Chrome (CH).

**Standards:** UL & CUL Listed


### ORDER NUMBER

Model #	Finish
HR-86	Xenon Bi-Pin
	BK Black
	BN Brushed Nickel
	CB Copper Bronze
HR-88	Halogen Bi-Pin
	CH Chrome
	DB Dark Bronze
	WT White



Example: HR-86-DB

### FINISHES



### CLASS 2 ENCLOSED ELECTRONIC TRANSFORMERS

Model	Input	Output	Dimensions
EN-1260-RB2	12V	1 x 60W	6 1/2" x 1 5/8" x 1 1/4"
EN-12120-RB2*	12V	2 x 60W	6" x 3 1/4" x 2 5/8"
EN-12180-RB2*	12V	3 x 60W	6 3/4" x 3 5/8" x 2 5/8"
EN-12300-RB2*	12V	5 x 60W	8 1/2" x 4 5/8" x 2 5/8"
EN-2460-RB2	24V AC	60W	6 1/2" x 1 5/8" x 1 1/4"
EN-24100-RB2	24V AC	96W	6 1/2" x 1 5/8" x 1 1/4"

\*Includes LED indicator lights and integral push in terminals

### UL LISTED CLASS 2 PLUG-IN ELECTRONIC TRANSFORMERS

EN-1260-P-AR	120V	12V, 60W	2 3/4" x 1 5/8" x 1 3/4"	BK Black WT White
EN-2460-P-AR	120V	24V AC/60W	2 3/4" x 1 5/8" x 1 3/4"	

### MULTIPLE TERMINAL BLOCK

Model #	Dimensions
MTB-01	L: 3 1/4" W: 1 3/4" H: 7/8"

12.5A max accommodates up to 3 output connections for 14 AWG wires.

### FROSTED LENS ACCESSORY

Model #	<input type="text"/>
LENS-45-FR-N	

Softens light and reduce glare

### WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585