


# HR-D329-S

## 3" Low Voltage Downlight Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Enclosed drop glass lens trim for use with HR-300 series low voltage downlight housings. Wet location listed for use in showers and similar environments.

### FEATURES

- Adjustable gimbal ring, 25° adjustment from vertical
- Die-cast aluminum construction with heavy gauge retention clips secure lens firmly to lamp
- Abrasion resistant powder coat paint or plated metal finish
- Variety of decorative and performance trim options
- Clear lens included
- UL & CUL Listed. Suitable for damp locations.

### SPECIFICATIONS

**Construction:** Powder coated or plated brushed nickel finish on die-cast aluminum. Fingered retention clips firmly hold trim to housing.

**Light Source:** Utilizes LED or Halogen 12V MR16 lamps, 35W max. Ordered separately.

**Standards:** UL & CUL Listed.

**Housings:** Non-IC housings require 3" of clearance from insulation on all sides. Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

### ORDER NUMBER

Model	Finish
HR-D329-S	WT White

**HR-D329-S** – **WT**

Example: **HR-D329-S-WT**

### LED MR16 (ORDER SEPARATELY)

<b>MR16LED-BAB</b>	<b>BK</b> <b>WT</b>
--------------------	------------------------

### LENSES & LOUVERS

Color Lens	<b>LENS-16-</b>	<b>AMB</b> Amber <b>BLU</b> Blue <b>GRN</b> Green <b>RED</b> Red <b>YEL</b> Yellow	UV Filter Frosted Lens Spread Lens Beam Elongating Lens Honeycomb Louver	<b>LENS-16-UVF</b> <b>LENS-16-FR</b> <b>LENS-16-SPR</b> <b>LENS-16-BEL</b> <b>LENS-16-HCL</b>
------------	-----------------	--	--	---

### 3" Low Voltage Housings (Required)

	Model	Transformer	Installation	Output	Rating	Volt
<p><i>Non-IC New Construction</i></p> <p><b>HR-302E</b> Electronic <b>HR-302M</b> Magnetic</p>	<ul style="list-style-type: none"> <li>• Integral Electronic or Magnetic Transformer</li> <li>• J-Box and Transformer Accessible Through Ceiling</li> <li>• Rated for Branch and Chain Wiring</li> <li>• Suitable for Damp Locations</li> <li>• Suitable for use in "Shallow" Joist Installations</li> </ul>	New Construction	12V, 50W max	Non-IC	120V	
<p><i>Non-IC Remodel</i></p> <p><b>HR-301E</b> Electronic</p>						
<p><i>Non-IC Remodel</i></p> <p><b>HR-301M</b> Magnetic</p>						

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

### WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585