
# HR-D418-S

# 4" Low Voltage Downlight Trim





### **PRODUCT DESCRIPTION**

Wet location listed drop glass lens trim. Typical applications include bathrooms, sauna's, workrooms and patios. For use with HR-8400 series low voltage housings.

### FEATURES

- Shower light with drop glass lens recessed downlight •
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 34" thick
- 5 year WAC Lighting product warranty

# WAC LIGHTING

## Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	
Location:	

### **SPECIFICATIONS**

**Construction:** Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Finish: Abrasion resistant powder coat painted or plated metal finish. Available in White (WT).

Standards: UL & CUL Listed, Suitable for wet locations

ORDER NUMBER		ACCESS	SORIES				
Model # HR-D418-S (Order lamp separately) HR-D418LED-S	Finish WT White	LENS-1	16- Color Lens	BLU Blue GRN Gree RED Rec	en LENS-16-	FRFrosted LetSPRSpread LetBELBeam Elon	ns gating Lens
(7W 450Im LED MR16 includ Model # HR-D418 -S	finish						
Example: <b>HR-D418LED-S-</b> 4" Low Voltage Housin		Model	Voltage	Transformer	Output	Installation	Rating
		HR-8402E	120V	Electronic	12V, 50W max		Non-IC
	<u>45%</u> 13%°	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585