


# HR-LED451TL – Invisible Trim™

## 4" LEDme® Open Reflector Downlight Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Square recessed trim with interior open reflector. Designed to sit flush with the ceiling for a clean, architectural look. For use with HR-LED418 Invisible Trim™ series housings.

### FEATURES

- Flush mount, no profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2 3/8"
- Narrow flood beam spread
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

**Light Source:** Utilizes six 3W LED's (included with housing). See individual housing for wattage rating.

**Finish:** Powder coat paint or plated metal finish. Available in White baffle w/White trim (WT/WT).

**Standards:** UL & CUL Listed.


### ORDER NUMBER

Model #	Finish	Reflector/Trim
HR-LED451TL	WT/WT	White/White

**HR-LED451TL – WT/WT**

Example: HR-LED451TL-WT/WT

### PHOTOMETRY



Beam Angle: 31.4°

### COMPATIBLE HOUSINGS (ORDER SEPARATELY)

Rating	Model #	Installation	Color Temp	Watt	Lumens	CRI	Input	Current	Dimensions	Cutout
IC-Rated	HR-LED418-NIC-SQ	New Construction	27 2700K	10.2W	639	85	120V 50/60Hz	450mA	L: 14 1/2"-24 1/2" W: 6 3/4" H: 5 1/2"	4 3/8"
			30 3000K		639	85				
	HR-LED418-RIC-SQ	Remodel	35 3500K		681	80				
			40 4000K		815	75				
Non-IC	HR-LED418-N-SQ	New Construction	27 2700K	16W	846	85	120V 50/60Hz	700mA	L: 14 1/2"-24 1/2" W: 6 3/4" H: 5 1/2"	4 3/8"
			30 3000K		846	85				
	HR-LED418-R-SQ	Remodel	35 3500K		901	80				
			40 4000K		1135	75				
Non-IC	HR-LED418-N-SQ	New Construction Emergency Backup Battery	27 2700K 30 3000K 35 3500K 40 4000K	EM 16W	846 846 901 1135	85 85 80 75	120V 50/60Hz	700mA	L: 14 1/2"-24 1/2" W: 11 1/8" H: 5 1/2"	4 3/8"

Example: HR-LED418-NIC-SQ27 or HR-LED418-NIC-SQ27-EM

See individual housing spec sheets for complete information.

WAC Lighting  
www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center  
1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585