


HR3LEDT318P

3.5" Tesla™ Pro LED 0°-30° Adjustable Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round 0° to 30° adjustable trim with interior open reflector.

FEATURES

- 3.5" aperture
- Energy Star® rated
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Power Consumption: 21.5W

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing.

Finish: Powder coated white
Electroplated brushed nickel and copper bronze

Standards: ETL & cETL Listed. See table below for Energy Star® qualifying products. Fixtures with * are Title 24 JA8-2016 Compliant.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish	
HR3LEDT318P 0° to 30° Adjustable	N 30°	827	2700K	85	1180	2472	Yes	
		927*	2700K	90	990	2104	Yes	
		830	3000K	85	1225	2555	Yes	
		930*	3000K	90	1115	2387	Yes	
		835	3500K	85	1330	2811	Yes	
		840	4000K	85	1335	2809	Yes	
	F 55°	827	2700K	85	1145	1364	Yes	
		927*	2700K	90	970	1165	Yes	
		830	3000K	85	1195	1428	Yes	
		930*	3000K	90	1085	1302	Yes	
		835	3500K	85	1290	1548	Yes	
		840	4000K	85	1310	1574	Yes	
		HBN Haze/Brushed Nickel HCB Haze/Copper Bronze HWT Haze/White BBN Specular Black/Brushed Nickel BCB Specular Black/Copper Bronze BWT Specular Black/White BN Brushed Nickel CB Copper Bronze WT White						



HR3LEDT318P

Example: HR3LEDT318PF835BN

COMPATIBLE HOUSINGS

See individual housing spec sheets for complete information.

New Construction

HR-3LED-H18D1-ICAC Narrow, IC-Rated, Airtight	120V-277V	HR-3LED-H18D1-ICAC Narrow, IC-Rated, Airtight Chicago Plenum	120V-277V
HR-3LED-H18D-ICAC IC-Rated, Airtight	120V-277V	HR-3LED-H18D-ICAC IC-Rated, Airtight Chicago Plenum	120V-277V
HR-3LED-H18D-EMICA IC-Rated, Airtight Emergency Backup Battery	120V	HR3LED-H18D-EMICAF IC-Rated, Airtight Emergency Backup Battery	277V

REPLACEMENT MODULES

Reflectors

Narrow Flood	SL-REF-BL10-1-N
Flood	SL-REF-BL10-1-F

LED

2700K (90 CRI)	BXRC-27G1000-B-23
2700K	BXRC-27E1000-B-23
3000K (90 CRI)	BXRC-30G1000-B-23
3000K	BXRC-30E1000-B-23
3500K	BXRC-35E1000-B-23
4000K	BXRC-40E1000-B-23

Remodel

HR-3LED-R22D Non-IC	120V-277V
------------------------	-----------

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760