RANGE – model: 164

120V Track MR16 Luminaire

WAC LIGHTING

Responsible Lighting®

| | | Fixture Type: |
|---|---------------|-----------------|
| | 61/8" | Catalog Number: |
| 2 | | Project: |
| | 31/2" 21/4" - | Location: |
| | | |

PRODUCT DESCRIPTION

Form follows function with instrument-like design and technology of the Range low voltage spot. Engineered to precision, these specification grade luminaires are ideal for commercial, hospitality and retail applications where high performance and vesatility are required.

FEATURES

- Available with LED lamp option
- 350° horizontal rotation and 90° vertical aiming with built-in degree scales, two aiming screws for locking aiming angle
- Easily re-lamped from the front
- Electronic transformer soft start feature is designed to prolong lamp life
- Threaded lens cap has three evenly spaced integral tension clips. Additional lens accessory support is provided by a separate check ring placed within the lens cap.
- Accommodates 1 lenses and 1 accessory (clear lens included)
- Dimmable
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum fixture with integral aiming indicators to assure precise directional adjustment.

Finish: Powder coat paint. Available in Black (BK) and White (WT).

Transformer: LED Version - 1W minimum load. Halogen Version - 20W minimum load (1W minimum load available. Consult factory for more details).

Lamp: 164L model uses 12V MR16, 75W max (not included). 164LED model uses 12V, 9W MR16 LED lamp (included). 490 lumens, 3000K CCT, 50,000 hour rated life, CRI: 90.

Dimming: With electronic low voltage (ELV) dimmer, LED lamp dims to 15%; Halogen lamp dims to 1%.

Standards: UL & CUL Listed, Patent Pending.

ORDER NUMBER

| System | Model # | Power | Lamp | Finisł | ı | |
|--------|-------------------------|---------------|----------------|----------|----------------|--|
| | rack rack 2 Track | 9W 75W max | LED Halogen | BK WT | Black White | |

ACCESSORIES



Example: LHT-164L-WT

| FINISHES | |
|----------|----|
| ВК | wт |
| | 1 |

| | | AMB | Amber | UV Filter Frosted Lens | LENS-16-UVF LENS-16-FR |
|---------------------|------------|--------------|--|-----------------------------------|----------------------------|
| | | BLU | Blue | Spread Lens | LENS-16-SPR |
| Color Lens LENS-16- | GRN RED | Green Red | Beam Elongating Lens Honeycomb Louver | LENS-16-BEL LENS-16-HCL | |
| | | YEL | Yellow | Cross Louver Wall Washing Hood | LENS-16-CRL HOOD-050-BK |

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. NOV 2017