



44 Harbor Park Drive Port Washington, NY 11050 Tel: 800.526.2588 www.waclighting.com

LED POWER SUPPLY

MODEL LD-700MA-03





Ordering Matrix LED Power supply	Constant current	Wattage	Dimmable	Remote Box
LD	700MA	03 = 3W	DIM	IS

Ordering Example (Model-Finish): LD-700MA03-EDIM-IS

Product Details

Compact and reliable class 2 constant current LED Description:

dimmable power unit for one 1*3W LED lights

Input Voltage: 120V AC 60Hz

Input Current: LD-700MA03-EDIM -IS 0.04A max

Output

2-5V DC Voltage:

Output

700mA DC constant current **Current:**

Load: LD-700MA03-EDIM -IS 1PCS 1x3W LED Fixtures

Dimension LD-700MA03-EDIM -IS L \times W \times H = 8 1/4" \times 1 3/4" \times 1 3/4"

Loading Wire: 22 AWG 6ft maximum length

Specification Features

- 700mA Constant Current for LED's optimized and stable performance.
- "Plug and Play" terminal blocks for wiring up to one LED lights.
- Open circuit, short circuit, overload and overheat protection.
- Input may used Electronic Lowvoltage dimmer to LED driver dimmable.(Example: LUTRON DVELV-300P)
- 5 year WAC Lighting product warranty


WAC Lighting reserves the right to modify the design of our products as part of the company's continuous improvement program.




44 Harbor Park Drive Port Washington, NY 11050 Tel: 800.526.2588 www.waclighting.com

LED POWER SUPPLY

MODEL LD-700MA-09





Ordering Matrix LED Power supply	Constant current	Wattage	Dimmable	Remote Box
LD	700MA	09 = 9W	DIM	IS

Ordering Example (Model-Finish): LD-700MA09-EDIM-IS

Product Details

Description: Compact and reliable class 2 constant current LED

dimmable power unit for up to three 1*3W LED lights

Input Voltage: 120V AC 60Hz

Input Current: LED-700MA09- EDIM -IS 0.13A max

Output

Voltage: 2-5V DC (Each Group)

Output

Current: 700mA DC constant current

Load: LD-700MA09-EDIM -IS 3PCS 1x3W LED Fixtures

Dimension LD-700MA09- EDIM -IS $L \times W \times H = 7 \frac{1}{4} \times 3 \frac{1}{8} \times 1 \frac{3}{4}$ "

Loading Wire: 22 AWG 6ft maximum length

Specification Features

- 700mA Constant Current for LED's optimized and stable performance.
- Three group output "Plug and Play" terminal blocks for wiring up to three LED lights.
- Open circuit, short circuit, overload and overheat protection.
- Input may used Electronic Lowvoltage dimmer to LED driver dimmable.(Example: LUTRON DVELV-300P)
- 5 year WAC Lighting product warranty

WAC Lighting reserves the right to modify the design of our products as part of the company's continuous improvement program.