InvisiLED® Daylight to Sunset

24V Color Changing LED Tape Light



Responsible Lighting®



5100K		595nm

Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

PRODUCT DESCRIPTION

Daylight to Sunset InvisiLED® is a color changing tape light that offers the unique ability to change the atmosphere of any interior space at a push of a button. Relax as the light segues from cool white to warm amber, mimicking the sun's gentle passage through the sky.

FEATURES

- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- DMX controller option (consult factory)
- · Wireless controller available
- · Select from any color to visibly change an interior design
- Switch to warm 3500K white light with the push of a button
- Run a program to change the speed and brightness
- · Minimum run length of 1' and maximum of 40'
- May be field cut every 6" at the end of a run
- · Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Flexible, silicone cased tape light. Peel and stick 3M

construction adhesive on back.

Indicating marks on back for field cutting.

Power Supply: Remote and plug-in electronic Class 2 transformers.

120VAC 50/60Hz input, 24V 60W output.

Light Source: 12 LEDs per foot

Dimming: May be dimmed with WAC wired (LED-TC-CTR-MSD)

/ wireless controller (LED-TO24-WS)

Operating Temp: $-4^{\circ}F - 122^{\circ}F$ ($-20^{\circ}C - 50^{\circ}C$), relative humidity 95%.


Standards: UL & CUL Listed for damp locations.

ORDER NUMBER - TAPE SECTION

Model	Watts/ft	Lumens/ft	Length	ı	Qty	Light	Color
LED-TC	1.5	75 Max	1 1-40 5	1 foot 1 foot 5 feet	1 40 1	WA	5100K to Amber

LED-TC- -WA

Example: LED-TC-5-WA



InvisiLED® Daylight to Sunset

Power Supplies and Accessories

WAC LIGHTING

Responsible Lighting®

Class 2 Power Supply (Required)

Type		Model	Input	Output	Max Run	Dim	
Remote	4	EN-2460D-C	120VAC	24VDC/60W	40 feet	Yes	Includes a 6 foot lead wire
Plug-in	ding.	EN-2460D-C-P	120VAC	24VDC/60W	40 feet	Yes	Includes a 6 foot lead wire

Controller

Controller (required)		LED-TC-CTR-MSD	5 feet	Switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Switch for master, slave and DMX functions A controller is needed for every 40 feet run
Wireless Controller(optional)	(1.5%) (1.5%) (1.5%) (1.5%)	LED-TO24-WS	5 feet	Wireless connection to Master Controller. Use to switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Uses 2 AAA batteries.
Signal Wire		LED-TC24-SW60 LED-TC24-SW120	5 feet 10 feet	Extends distance between Master Controller and Slave Controller Consult factory for DMX controller options

Accessories

Aluminum Channel		LED-T-CH	5 feet	Includes a diffuser, two end caps, and five screws
Deep Aluminum Channel		LED-T-CH1	5 feet	Includes a diffuser, two end caps, and five screws
45° Angled Aluminum Channel		LED-T-CH2	5 feet	Includes a diffuser, two end caps, and five screws
Fixed Angle Channel Clip	60	LED-T-CL3-PT	5 feet	Used to mount any aluminum channel Includes 2 pieces, 4 screws
Adjustable Channel Clip		LED-T-CL2-PT	5 feet	Used to mount any aluminum channel Adjusts 50° from center either way Includes 2 pieces, 4 screws
Retrofit Channel		LED-T-RC	3 feet	Creates fixed curves
Clip	3	LED-T-CL	10 pcs	Holds the tape from the underside Includes 10 pieces, 10 screws
Curve Clip		LED-T-CL1	10 pcs	Runs over the tape to secure the angled tape Includes 2 pieces, 4 screws

Signal Wire LED-TC24-SW60 LED-TC24-SW120		Extends distance between Master Controller and Slave Controller Consult factory for DMX controller options
Low Voltage Wiring Box	L: 1½ in W: ¾ in H: ⅙ in	Neatly houses up to two wires
Wiring Box With Switch	L: 6¼ in W:15% in H: 1¼ in	Use when spanning a large gap in a system layout without leaving exposed wiring

Joiner Cable		LED-TC-IC2 LED-TC-IC6 LED-TC-IC12 LED-TC-IC36 LED-TC-IC72	2 in 6 in 12 in Connects 136 in tape sections 72 in
3-Way "Y" Connector	Y	LED-TC-Y	Connects tape sections
4-Way "X" Connector	+	LED-TC-X	Connects tape sections
"L" Connector	9	LED-TC-L	Connects tape sections
End cap		LED-TC-EC	1 cut end cap 1 male end cap