

SMASH - Mini LED Pendant

PD-12911

dweLED

by WAC Lighting



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

An alluring pendant all on its own, or in multiples.

FEATURES

- Double acrylic diffuser enclosed design
- Thin powered aircraft cables provide an ultra-clean look
- 2.76" x 1.26" x 1.18" universal voltage driver (120V - 277V) installs within junction box
- Color Temperature: 3000K
- CRI: 90
- Rated Life: 42,000 hours

Replacement

RPL-SHA-12911	<i>Fabric Shade</i>
RPL-GLA-12911	<i>Glass</i>
RPL-DIF-12911	<i>Diffuser</i>

SPECIFICATIONS

Construction: Aluminum with acrylic diffuser

Input: 120V - 277V


Dimming (120V): 100% - 10% ELV / 0-10V / Triac

Dimming (277V): 100% - 10% 0-10V

Light Source: High output LED

Finish: Black (BK), Chrome (CH)

Standards: ETL/cETL, Damp location listed, Title 24 Compliant



PD-12911

ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finish
PD-12911	11"	5.7W	390	340	BK <i>Black</i> CH <i>Chrome</i>

Example: **PD-12911-BK**

dweLED.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760