

NIVEOUS - LED Pendant

PD-52307, PD-52310, PD-52313

dweLED

by WAC Lighting



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The perfect sphere.




FEATURES

- Mouth blown etched opal glass provides even illumination
- Integral swivel for sloped ceiling
- Driver located in standard 4" junction box
- Three 12" and one 6" downrods included (additional downrods available)
- 2.95" x 1.88" x 1.14" universal driver (120V - 220V - 277V)
- Color Temperature: 3000K (2700K/3500K special order)
- CRI: 90
- Rated Life: 70,000 hours
- Supplied with 114" of wire

Replacement

RPL-GLA-52307	Glass
RPL-GLA-52310	Glass
RPL-GLA-52313	Glass
RPL-ROD-IN06-BN	Rod
RPL-ROD-IN12-BN	Rod
RPL-ROD-IN06-AB	Rod
RPL-ROD-IN12-AB	Rod
RPL-ROD-IN06-WT	Rod
RPL-ROD-IN12-WT	Rod

ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finish
PD-52307	7"	10W	777	588	BN brushed Nickel 
PD-52310	10"	14W	906	685	WT White 
PD-52313	13"	14W	906	715	AB Aged brass 

Example: **PD-52310-BN**

For 2700K option, add "-27"; 3500K add "-35" before the finish: **PD-52310-27-BN**

SPECIFICATIONS

Construction: Aluminum with acrylic diffuser


Input: 120V - 277V

Dimming: 100% - 10% ELV

Light Source: High output LED


Finish: Brushed Nickel (BN), White (WT), Aged Brass (AB)

Standards: ETL/cETL, Damp location listed




PD-52307

Min 16"
Max 108"



PD-52310

Min 19"
Max 108"



PD-52313

Min 22"
Max 108"

*Driver installs within junction box

dweLED.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760