


R-420

4" Line Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Recessed trim with interior step baffle. For use with R-400 series Line voltage downlight housings.

FEATURES

- Durable stamped metal construction
- Retention clips hold trim firmly to housing
- Abrasion resistant powder coat paint or plated metal finish
- Handles surfaces up to 3/4"
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable stamped metal construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED PAR20 lamp or medium base incandescent. Incandescent lamps are rated for up to 50W watts max. Compact Fluorescent lamps are rated for 13 watts max. Lamps are ordered separately.

Finish: Abrasion resistant powder coat painted or plated metal finish. Trim is available in Brushed Nickel (BN), Copper Bronze (CB) or White (WT).

Standards: UL & CUL Listed. Suitable for damp locations.

ORDER NUMBER

Model	Finish	Baffle/Trim
R-420	BN	Brushed Nickel/Brushed Nickel
	CB	Copper Bronze/Copper Bronze
	WT/WT	White/White

R-420 -

Example: R-420-BN

FINISHES



LED PAR20 LAMP (ORDER SEPARATELY)

PAR20LED-10N30	BK	Black
	WT	White

4" Line Voltage Housings (Required)

	Model	Installation	Rating	Voltage
<p><i>IC-Rated New Construction</i></p>	R-4025-N-ICA	New Construction	IC – Airtight Ready	120V
<p><i>Non-IC New Construction</i></p>	R-4005-N-A	New Construction	Non-IC – Airtight Ready	
<p><i>Non-IC Remodel</i></p>	R-4015-R-A	Remodel	Non-IC – Airtight Ready	

Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585