

# HR-2LED-T309

2" Tesla™ LED 0°-30° Adjustable Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, round 0° to 30° adjustable trim with interior open reflector.

## FEATURES

- 2" aperture
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 14.5W LED, CRI: 85 & 90+

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)


**Mounting:** Two heavy gauge retention clips hold trim firmly to housing

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed

See table below for California Title 24 Compliant for qualifying products.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	2013 Title 24	Finish
HR-2LED-T309 0°-30° Adjustable	S 15°	<b>27</b> 2700K	85	520	3026	No	<b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White 
		<b>W</b> 3000K	85	565	3375	No	
		<b>9W</b> 3000K	90	520	2684	No	
		<b>35</b> 3500K	85	590	3521	No	
	N 26°	<b>C</b> 4000K	85	545	3848	No	
		<b>27</b> 2700K	85	515	1598	No	
		<b>W</b> 3000K	85	550	1729	No	
		<b>9W</b> 3000K	90	543	1644	Yes	
	F 45°	<b>35</b> 3500K	85	575	1831	No	
		<b>C</b> 4000K	85	520	1770	No	
		<b>27</b> 2700K	85	510	913	No	
		<b>W</b> 3000K	85	545	976	No	
	F 45°	<b>9W</b> 3000K	90	570	975	Yes	
		<b>35</b> 3500K	85	560	998	No	
		<b>C</b> 4000K	85	555	1113	No	

**HR-2LED-T309**  -  -

Example: HR-2LED-T309F-9W-BN

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

New Construction

<b>HR-2LED-H09D-ICA</b> IC-Rated, Airtight 120V-277V	<b>HR-2LED-H09D-ICAC</b> IC-Rated, Airtight Chicago Plenum 120V-277V
--	---

Remodel

<b>HR-2LED-R14D</b> Non-IC 120V-277V
--

**REPLACEMENT MODULES**

Reflectors

Spot Narrow Flood Flood	<b>SL-REF-LUX10-S</b> <b>SL-REF-LUX10-N</b> <b>SL-REF-LUX10-F</b>
-------------------------------	---

LED

2700K	85 CRI	<b>LXS8-PW27</b>
3000K	85 CRI	<b>LXS8-PW30</b>
3000K	90 CRI	<b>LXS9-PW30</b>
3500K	85 CRI	<b>LXS8-PW35</b>
4000K	85 CRI	<b>LXS8-PW40</b>

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760